## CLAIMS

1. Variable phase-shifting circuit comprising:

an input receiving an input signal having a specified oscillation frequency,

an output delivering an output signal having said specified oscillation frequency (Fin) and having a variable phase shift with respect to said input signal,

at least one control input receiving a control signal which controls the phase-shift of said output signal with respect to said input signal,

a synchronized oscillator having at least a synchronization input coupled to said input of the variable phase-shifting circuit, at least an output coupled to said output of the variable phase-shifting circuit, said synchronized oscillator having a variable free-running oscillation frequency controlled by said control signal.

2. The circuit of Claim 1, wherein the synchronized oscillator further comprises an astable multivibrator circuit having a first branch and a second branch arranged in parallel between a positive supply terminal and a negative supply terminal or ground, means delivering into the first branch and into the second branch, a respective quiescent current of the same specified value, said quiescent current being controlled by the control signal.

3. The circuit of Claim 2, wherein, for each branch, the means delivering a quiescent current into the branch comprises a respective current source arranged in series in the branch, which delivers a current of a specified value, and in wherein the control signal is a current control signal which is added to said current of a specified value.

4. Phase interpolator comprising:

- a signal output which delivers an output signal;- at least one data input receiving a digital input value coded in P bits, where P is an integer, representing the difference between an actual instant of switching of a pulse of a signal to be interpolated and a desired instant of switching said output signal;

- N1 first variable phase-shifting circuits, where N1 is an integer strictly greater than one, each comprising an input which receives an input signal having the frequency of a reference signal, the input signals received by said respective inputs of said N1 variable phase-shifting circuits being respectively phase-shifted by 360°/N1, each variable phase-shifting circuit further comprising a control input receiving a control signal and an output which delivers an output signal corresponding to the signal received at the input phase-shifted based on said control signal, and each variable phase-shifting circuit comprising a synchronized oscillator having at least one synchronization input coupled to said variable phase-shifting circuit input , at least one output coupled to the said output of the variable phase-shifting circuit, said synchronized oscillator having a variable free-running oscillation frequency which is controlled by said control signal;

- a multiplexer having N1 inputs which receive the N1 signals delivered by the respective output of the N1 variable phase-shifting circuits and an output which delivers one of the said N1 signals based on the value of a given number Q of the most significant bits of the digital input value, where Q is an integer less than or equal to P.

5. The phase interpolator of Claim 4, further comprising a digital/analog converter having P-Q inputs which receive the P-Q least significant bits of the digital input value, and having an output which delivers, based on the value of said P-Q bits, an analog phase-shift correction signal which is delivered at the control input of at least one of the N1 first variable phase-shifting circuits.

6. The phase interpolator of Claim 4 wherein the phase-shift correction signal is delivered at the control input of each of the N1 first variable phase-shifting circuits.

7. The phase interpolator of Claim 4 further comprising a demultiplexer having an input receiving the phase-shift correction signal, at least N1 outputs respectively coupled to the control input of the N1 first variable phase-shifting circuits, and directing the phase-shift correction signal

to the control input of one of the said N1 first variable phase-shifting circuits based on the value of the Q most significant bits of the digital input value.

8. The phase interpolator of Claim 4, further comprising a multiphase clock generator comprising:

- N1 second variable phase-shifting circuits identical to the N1 first variable phase-shifting circuits, connected in series via their respective inputs and outputs, the input of a first of said N1 second variable phase-shifting circuits receiving the reference signal;

- a phase comparator having a first input which receives the reference signal, a second input which is connected to the output of a last one of said N1 second variable phase-shifting circuits, and an output;

- a low-pass filter with an input coupled to the output of said phase comparator, and an output;

- an adaptation module having an input coupled to the output of said low-pass filter and at least N1 first outputs delivering N1 identical first calibration signals respectively, which are applied to the respective control inputs of said N1 second variable phase-shifting circuits.

9. The phase interpolator of Claim 8, wherein the adaptation module of the multiphase clock generator further comprises an N1 + 1-th output, delivering an N1 + 1-th calibration signal identical to the calibration signals generated by the N1 first outputs, and coupled to the digital-analog converter.

10. The phase interpolator of Claim 4 further comprising calibration means comprising:

- N2 third variable phase-shifting circuits identical to the N1 first variable phase-shifting circuits, connected in series via their respective inputs and outputs, the input of a first of said N2 third variable phase-shifting circuits receiving the reference signal;

- a phase comparator having a first input which receives the reference signal, a second input which is connected to the output of a last one of said N2 third variable phase-shifting circuits, and an output;

- a low-pass filter having an input coupled to the output of said phase comparator, and an output;

- an adaptation module having an input coupled to the output of said low-pass filter and at least N2 + 1 outputs delivering N2 + 1 identical second calibration signals respectively, among which N2 outputs are coupled to the respective control inputs of said N2 third variable phase-shifting circuits.

11. The phase interpolator of Claim 10, wherein the adaptation module of the calibration means includes N2 + 1 outputs delivering respectively N2 + 1 identical second calibration signals among which, in addition, the N2 + 1-th output is coupled to the digital-analog converter so as to provide it with a second reference value.

12. The phase interpolator of Claim 10, wherein the adaptation module of the calibration means includes N2 + 2xN1 outputs delivering respectively N2 + 2xN1 identical second calibration signals, among which, N1 other outputs are further coupled to the respective control inputs of the N1 second variable phase-shifting circuits of the multiphase clock generator, and among which N1 other outputs are coupled to the respective control inputs of the N1 first variable phase-shifting circuits.

13. The phase interpolator of Claim 4, wherein further comprising an input receiving a signal for activating/deactivating the multiplexer, to control the frequency of the output signal with respect to the reference signal frequency.

14. Digital frequency synthesizer comprising a phase accumulator and a phase interpolator coupled to said phase accumulator, wherein said phase interpolator comprises :

- a signal output which delivers an output signal;

- at least one data input receiving a digital input value coded in P bits, where P is an integer, representing the difference between an actual instant of switching of a pulse of a signal to be interpolated and a desired instant of switching said output signal;

- N1 first variable phase-shifting circuits, where N1 is an integer strictly greater than one, each comprising an input which receives an input signal having the frequency of a reference signal, the input signals received by said respective inputs of said N1 variable phase-shifting circuits being respectively phase-shifted by 360°/N1, each variable phase-shifting circuit further comprising a control input receiving a control signal and an output which delivers an output signal corresponding to the signal received at the input phase-shifted based on said control signal, and each variable phase-shifting circuit comprising a synchronized oscillator having at least one synchronization input coupled to said variable phase-shifting circuit input, at least one output coupled to the said output of the variable phase-shifting circuit, said synchronized oscillator having a variable free-running oscillation frequency which is controlled by said control signal;

- a multiplexer having N1 inputs which receive the N1 signals delivered by the respective output of the N1 variable phase-shifting circuits and an output which delivers one of the said N1 signals based on the value of a given number Q of the most significant bits of the digital input value, where Q is an integer less than or equal to P.

15. The Digital frequency synthesizer of Claim 14, wherein the phase interpolator, further comprises a digital/analog converter having P-Q inputs which receive the P-Q least significant bits of the digital input value, and having an output which delivers, based on the value of said P-Q bits, an analog phase-shift correction signal which is delivered at the control input of at least one of the N1 first available phase-shifting circuits.

16. The Digital frequency synthesizer of Claim 14, wherein the phase-shift correction signal is delivered at the control input of each of the N1 first variable phase-shifting circuits.

17. The Digital frequency synthesizer of Claim 14, further comprising a demultiplexer having an input receiving the phase-shift correction signal, at least N1 outputs respectively coupled to the control input of the N1 first variable phase-shifting circuits, and directing the phase-

shift correction signal to the control input of one of the said N1 first variable phase-shifting circuits based on the value of the Q most significant bits of the digital input value.

18. The Digital frequency synthesize of Claim 14, further comprising a multiphase clock generator comprising:

- N1 second variable phase-shifting circuits identical to the N1 first variable phase-shifting circuits, connected in series via their respective inputs and outputs, the input of a first of said N1 second variable phase-shifting circuits receiving the reference signal;

-a phase comparator having a first input which receives the reference signal, a second input which is connected to the output of a last one of said N1 second variable phase-shifting circuits; and an output;

- a low-pass filter with an input coupled to the output of said phase comparator, and an output;

- an adaptation module having an input coupled to the output of said low-pass filter and at least N1 first outputs delivering N1 identical first calibration signals respectively, which are applied to the respective control inputs of said N1 second variable phase-shifting circuits.

19. The Digital frequency synthesizer of Claim 18, wherein the adaptation module of the multiphase clock generator further comprises an N1 + 1-th output, delivering an N1 + 1-th calibration signal identical to the calibration signals generated by the N1 first outputs, and coupled to the digital-analog converter.

20. The Digital frequency synthesize of Claim 14 further comprising calibration means comprising:

- N2 third variable phase-shifting circuits identical to the N1 first variable phase-shifting circuits, connected in series via their respective inputs and outputs, the input of a first of said N2 third variable phase-shifting circuits receiving the reference signal;

- a phase comparator having a first input which receives the reference signal, a second input which is connected to the output of a last

one of said N2 third variable phase-shifting circuits, and an output;

- a low-pass filter having an input coupled to the output of said phase comparator, and an output;

- an adaptation module having an input coupled to the output of said low-pass filter and at least N2 + 1 outputs delivering N2 + 1 identical second calibration signals respectively, among which N2 outputs are coupled to the respective control inputs of said N2 third variable phase-shifting circuits.

21. The Digital frequency synthesizer of Claim 20, wherein the adaptation module of the calibration means includes N2 + 1 outputs delivering respectively N2 + 1 identical second calibration signals among which, in addition, the N2 + 1-th output is coupled to the digital-analog converter so as to provide it with a second reference value.

22. The Digital frequency synthesizer of Claim 20, wherein the adaptation module of the calibration means includes N2 + 2xN1 outputs delivering respectively N2 + 2xN1 identical second calibration signals, among which, N1 other outputs are further coupled to the respective control inputs of the N1 second variable phase-shifting circuits of the multiphase clock generator, and among which N1 other outputs are coupled to the respective control inputs of the N1 first variable phase-shifting circuits.

23. The Digital frequency synthesizer of Claim 14, wherein further comprising an input receiving a signal for activating/deactivating the multiplexer, to control the frequency of the output signal with respect to the reference signal frequency.